

Solar Home Lighting System SHLS-L2

- **Maximum Power Point Tracking Technology (MPPT)**
- **Maintains CC - CV**
- **Peak efficiency 95%**
- **Reverse polarity protection**
- **Battery monitoring system**
- **SOC- and -voltage -control LVD**
- **Over charge and discharge protection**
- **Load short circuit protection / Overload protection**
- **Lighting protection**
- **Compact in size**
- **USB output to charge mobile, MP3, and Etc.**

Model	SHLS-L3
Charging Type	Pulse width modulation (PWM)
Panel power	5Wp
Maximum panel voltage [VOC]	21V (Over voltage protection by varistor)
Battery Type	SMF
Battery Capacity	4.5 Ah
Battery Protection	Active HVD and LVD , Inbuilt BMS circuit
High Voltage Protection	7 V
Low Voltage Protection	6.3 V
Efficiency	>95% peak
Max Charging current	3 A
Max Discharging current	3 A
DC load nominal Voltage	6 V DC
Electronic Protection	PV Reverse polarity, Reverse current flow at night, Surge Transient, Load short, over current, High and Low voltage protection at battery side.
LED Indications	Green : Solar Yellow : Battery SOC Red : Fault indication
Ambient Temperature	0°C to +50°C while charging ; -20°C to +50°C while dis-charging
Protection	IP 22
USB connector	USB Type A 5.5 V ; 500mA
Load	DC jack 6.5mm – 2 output terminals
Weight in Kg	2.50 Kg
Dimension (L X W X H) mm	350 x 250 x 115
Accessories	Panel with cable – 1No, DC LED Lamp 1.5W – 2 Nos, E-27 Lamp holder assembly and mobile charging connector – 1No.
In built led lamp in unit	Inbuilt Led 3w lamp in unit

Deshmukh Solar Energy Pvt Ltd

Factory - Gat No- 104, Vinchur Gavli Road, Opp. Adgaon Substation, Nashik-422 003, Maharashtra, India.
 info@deshmukhenergy.com phone – 91 9225530444